

DESCRIPTION

Johnstone's Trade Covaplus Vinyl Matt is a high-quality matt emulsion that is suitable for all interior walls and ceilings. Its superior opacity* gives great hiding power, making it easy to cover surfaces. The product has outstanding coverage which means it goes further, so less paint is required. The superior flow* makes it easy to apply by brush, roller and spray to achieve a great finish.

* Compared to the previous Johnstone's Trade Covaplus Vinyl Matt formula.

RECOMMENDED USES



Suitable for interior use on walls and ceilings.

TYPE OF SUBSTRATE

Suitable to use on plaster, wallboards, concrete, cement rendering, brickwork and blockwork in internal situations.

COLOUR RANGE

Available in a full colour palette via the Johnstone's Tinting System.

FINISH

Matt.

VOLUME SOLID

53.7%

COVERAGE



Johnstone's Trade Covaplus will cover up to 17 square metres per litre depending on the nature and porosity of the surface being painted.

FILM THICKNESS

Wet: 90um Dry: 30um.

DRYING TIME



Touch dry in 1-2 hours.
Recoat after 2-4 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. PROTECT FROM FROST

THINNER

Thinner: Clean water.

VOC CONTENT

EU limit value for this product (Cat A/a): 30g/l (2010) This product contains max 3g/l VOC



KEY PROPERTIES

- Superior Opacity and covering power*
- Superior Coverage at 17m² per litre*
- Superior Flow for easier application*

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Prime bare surfaces with the appropriate Johnstone's Trade Primer. Rub down previously gloss painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Ensure good ventilation during application and drying. Do not breathe spray. Wear respiratory protection. Stir well. Easy to apply by brush or roller. Also suitable for application by spray. Seal absorbent surfaces with a coat of Johnstone's Trade Covaplus thinned up to 10% with clean water. If more than one can of a colour is to be used in the same area, intermix before use. Do not apply in temperatures below 10°C.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- Do not breathe spray. Wear respiratory protection
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZES

1 Litre, 2.5 Litre, 5 Litre, 10 Litre.
350ml tester pots available.