

DESCRIPTION

Keep paint surfaces looking fresh for longer, thanks to Easy Clean Technology which allows dirt and contaminants to be easily cleaned off the painted surface. The premium paint binder prevents stains from seeping into your paint surface, making them easy to clean and remove with soap, water and a soft cloth for up to 10,000 scrub cycles. Johnstone's Trade Cleanable Matt gives a true matt finish when first painted, and continues to stay matt after cleaning.

RECOMMENDED USES



Suitable for interior use on walls and ceilings.

TYPE OF SUBSTRATE

Suitable for use on wallboards, concrete, brickwork and blockwork in internal situations. Also suitable for primed wood and metal.

COLOUR RANGE

Full colour offer available via the Johnstone's Tinting System

FINISH

Matt

VOLUME SOLID

46%

COVERAGE



Johnstone's Trade Cleanable Matt will cover up to 15 square metres per litre depending on the nature and porosity of the surface being painted.

FILM THICKNESS

Wet: 70µm, dry: 32µm

DRYING TIME



Touch dry in 2 hours. Recoatable after 4 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Do not use empty container for storing food. PROTECT FROM FROST.

THINNER

Thinner: Clean water.

VOC CONTENT

EU limit value for this product (Cat A/a): 30g/l (2010). This product contains a maximum of 10 g/l VOC.



KEY PROPERTIES

- Superior cleanability
- Excellent stain resistance
- Lasting durability. Scrub Class 1 ISO 11998
- True matt finish that stays matt after cleaning
- Improved Opacity

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Rub down previously glossy painted surfaces with fine waterproof abrasive paper to remove sheen and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Ensure good ventilation during application and drying. Do not breathe spray. Wear respiratory protection. Stir well. Easy to apply by brush or roller. Also suitable for application by spray. Seal absorbent surfaces such as new plaster with a coat of Johnstone's Trade Cleanable Matt thinned up to 20% with clean water. Do not apply in temperatures below 10°C or in damp conditions.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

CLEANING STAINS

Apply all-purpose non bleach cleaner to sponge or soft cloth. Wipe away stain using smooth circular motions with light pressure. Always rinse with clean water and wipe dry to leave the surface clean and free from smears.

SIZES

2.5 Litre, 5 Litre & 10 Litre.